




CWMAG 2023

# Paper 9 – Pump Design and Optimisation

By Ashley Upton and Andy Aung - HydroCo

# Paper Overview



## UK Water Industry Challenges

Water companies to be net zero by 2030

Water industry uses 3% of UK's energy

Largest consumption from distribution of water in networks

4th most energy intensive sector in the UK

Industry only generates 8.5% from renewable sources.

Sources: UK Government

# Borehole Optimisation Study

## Scope:

- Review the client's borehole sites
- Rank on power consumption
- Select 6 highest consuming sites

## Target:

- Reduce overall site operational costs by 5%



Model	Message
	Booster Pump no
	Booster Pump no 2
	Booster Pump no 1
	Booster Pump no 2
	Booster Pump no 3
	Booster Pump no 4
	Borehole Pump 1
	Borehole Pump 2
	Borehole Pump 1
	Borehole Pump 2
	Borehole Pump 3
	Borehole Pump no 1
	Borehole Pump no 2
	Borehole Pump no 1
	Borehole Pump no 2
	Borehole Pump no 3
	Borehole Pump 1
	Borehole Pump 2
	Borehole Pump no 1
	Borehole Pump no 2
	Borehole Pump no 3
	Borehole Pump 2
	Borehole Pump 3
	Borehole Pump 4
	Borehole Pump 1
	Borehole Pump 2
	Borehole Pump 3
	Borehole Pump 4
	Borehole Pump 1
	Borehole Pump 2
	Borehole Pump 3
	Borehole Pump 4
	Borehole Pump 1
	Borehole Pump 2
	Borehole Pump 3
	Borehole Pump 4
	High IR Pump no 2
	High IR Pump no 3
	High IR Pump no 4
	High IR Pump no 5
	High IR Pump no 6
	Low IR Pump no 2
	Low IR Pump no 3
	Low IR Pump no 4
	Low IR Pump no 5
	Low IR Pump no 6
	Low IR Pump no 7
	Low IR Pump no 8
	Low IR Pump no 9
	Low IR Pump no 10
	Low IR Pump no 11
	Low IR Pump no 12
	Low IR Pump no 13
	Low IR Pump no 14
	Low IR Pump no 15
	Low IR Pump no 16
	Low IR Pump no 17
	Low IR Pump no 18
	Low IR Pump no 19
	Low IR Pump no 20
	Low IR Pump no 21
	Low IR Pump no 22
	Low IR Pump no 23
	Low IR Pump no 24
	Low IR Pump no 25
	Low IR Pump no 26
	Low IR Pump no 27
	Low IR Pump no 28
	Low IR Pump no 29
	Low IR Pump no 30
	Low IR Pump no 31
	Low IR Pump no 32
	Low IR Pump no 33
	Low IR Pump no 34
	Low IR Pump no 35
	Low IR Pump no 36
	Low IR Pump no 37
	Low IR Pump no 38
	Low IR Pump no 39
	Low IR Pump no 40
	Low IR Pump no 41
	Low IR Pump no 42
	Low IR Pump no 43
	Low IR Pump no 44
	Low IR Pump no 45
	Low IR Pump no 46
	Low IR Pump no 47
	Low IR Pump no 48
	Low IR Pump no 49
	Low IR Pump no 50
	Low IR Pump no 51
	Low IR Pump no 52
	Low IR Pump no 53
	Low IR Pump no 54
	Low IR Pump no 55
	Low IR Pump no 56
	Low IR Pump no 57
	Low IR Pump no 58
	Low IR Pump no 59
	Low IR Pump no 60
	Low IR Pump no 61
	Low IR Pump no 62
	Low IR Pump no 63
	Low IR Pump no 64
	Low IR Pump no 65
	Low IR Pump no 66
	Low IR Pump no 67
	Low IR Pump no 68
	Low IR Pump no 69
	Low IR Pump no 70
	Low IR Pump no 71
	Low IR Pump no 72
	Low IR Pump no 73
	Low IR Pump no 74
	Low IR Pump no 75
	Low IR Pump no 76
	Low IR Pump no 77
	Low IR Pump no 78
	Low IR Pump no 79
	Low IR Pump no 80
	Low IR Pump no 81
	Low IR Pump no 82
	Low IR Pump no 83
	Low IR Pump no 84
	Low IR Pump no 85
	Low IR Pump no 86
	Low IR Pump no 87
	Low IR Pump no 88
	Low IR Pump no 89
	Low IR Pump no 90
	Low IR Pump no 91
	Low IR Pump no 92
	Low IR Pump no 93
	Low IR Pump no 94
	Low IR Pump no 95
	Low IR Pump no 96
	Low IR Pump no 97
	Low IR Pump no 98
	Low IR Pump no 99
	Low IR Pump no 100



# Measuring The Existing System

Visiting the site with the aim to:



- Understand system
- Data collection
- Data verification






# Measuring The Existing System

- Borehole pump assessment
  - Well drawdown
  - Water level variance
  - Influences maximum and minimum pump lift






# Reducing System Losses

- Condition of the assets
- Type of assets
- Remove unwanted headloss



# Reducing System Losses - Site Model Calibration

- Create a model of the site
- Calibrate using measured data
- Identify significant headlosses
- Assess existing pump performance







# Design Optimum Pumps



What does the client want from the site?

- 1 • Pumping more, or less water
- 2 • Reducing electricity bills
- 3 • Change in operation:
  - Sending water somewhere else?
- 4 • Network calming
- 5 • Backup pumps



# Design Optimum Pumps – Defining the system curve



- 1
- 2
- 3
- 4
- 5



Proposed site operation: BH3, 17.99 MLD over 21 hours, 20.5 MLD over 24 hours (238 l/s)  
 BH3+BH1, 28 MLD over 24 hours

# Design Optimum Pumps - Defining The Duty Point

Pump Performance vs Efficiency





- ✕ BH1 & BH3 at 28MLD
- ✕ BH3 at 20.55MLD

KEY			
	100% SPEED		60% SPEED
	90% SPEED		50% SPEED
	80% SPEED		MOST EFFICIENT POINT
	70% SPEED		

# Design Optimum Pumps - Defining The Duty Point

Pump Performance vs Efficiency





- ✕ BH1 & BH3 at 28MLD
- ✕ BH3 at 20.55MLD

KEY			
	100% SPEED		60% SPEED
	90% SPEED		50% SPEED
	80% SPEED		MOST EFFICIENT POINT
	70% SPEED		



# Design Optimum Pumps - Defining The Duty Point


- 1
- 2
- 3
- 4
- 5



- ✕ BH1 & BH3 at 28MLD
- ✕ BH3 at 20.55MLD

KEY			
	100% SPEED		60% SPEED
	90% SPEED		50% SPEED
	80% SPEED		MOST EFFICIENT POINT
	70% SPEED		

# Collect Manufacturers 'Best Offering'




Existing Pump:  
275 kW  
£1,395 per day  
(inc. site headloss)

Design Pump:  
163 kW  
£930 per day  
(exc. site headloss)

Manufacturers Best  
Pump:  
160 kW  
£912 per day

35% Saving Achieved

# Optimum Pump Selection - Composition Of Pumped Energy



## Pump Efficiency

Energy dependent on the efficiency of the pump


## System Losses

Energy required to overcome system losses

## Static Lift


Energy required to get water out of ground into storage with no headloss.

# Borehole Optimisation Conclusions







# Case Study - System Step Change



Res 1,2 & 3





PS1



# Case Study - Pump Configuration

Operating Conditions		Liquid	
Flow, rated	: 212.2 l/s	Liquid Type/ Application	: Water
Differential Head (requested)	: 100.3 m	Additional liquid description	:
Differential Head (actual)	: 100.4 m	Solids diameter, max	: 0.00 mm
Suction pressure, rated / max	: 0.00 / 0.00 bar.g	Solids/Bagasse/Stock consistency by volume	: 0.00 %
NPSH available, rated	: Ample	Temperature, max	: 20.00 deg C
Site Supply Frequency	: 50 Hz	Fluid density rated	: 1.000 SG
<b>Performance</b>		Viscosity, rated	: 1.00 cSt
Speed, rated	: 1346 rpm	Vapor pressure, rated	: 0.02 bar.a
Impeller diameter, rated (approx.)	: 600 mm	<b>Material</b>	
Impeller diameter, maximum	: 600 mm	Material selected	: Grey Cast Iron / Stainless Steel / Stainless Steel
Impeller diameter, minimum	: 490 mm	<b>Pressure Data</b>	
Efficiency	: 85.49 %	Maximum working pressure	: 10.88 bar.g
NPSH required / margin required	: 3.91 / 0.50 m	Maximum allowable working pressure	: 19.00 bar.g
nq (imp, eye flow) / S (imp, eye flow)	: 14 / 154 Metric units	Maximum allowable suction pressure	: 14.00 bar.g
Minimum Continuous Safe Flow (MCSF)	: -	Hydrostatic test pressure	: 16.32 bar.g
Head, maximum, rated diameter (approx.)	: 111.1 m	<b>Driver &amp; Power Data (@Max density)</b>	
Head rise to shutoff (approx.)	: 10.69 %	Driver sizing specification	: Rated power
Flow, best eff. point	: 218.2 l/s	Margin over specification	: 15.00 %
Flow ratio, rated / BEP	: 97.27 %	Service factor	: 1.00
Diameter ratio (rated / max)	: 100.00 %	Power, hydraulic	: 209 kW
Head ratio (rated dia / max dia)	: 100.00 %	Power, rated	: 244 kW
Cq/Ch/Ce/Cn [HL2010]	: 1.00 / 1.00 / 1.00 / 1.00	Power, maximum, rated diameter	: 327 kW
Selection status	: Acceptable	Minimum recommended driver rating	: 315 kW / 422 hp
Performance testing standard	: -		



Pump Curve \_Pump\_new\_v2

Pump Curve Notes

Pump Curve Data

Nominal Flow (l/s) 212.20 Pressure Diameter (mm) 700.00 Inertia Mode User value

Nominal Speed (rpm) 1346 Suction Diameter (mm) 800.00 Total Inertia (kg.m2) 0.00

Flow (l/s)	Head (m)	Mechanical Power (kW)
0.00	110.00	100.00
73.23	109.83	128.00
107.97	109.26	156.00
142.71	107.87	184.00
177.46	105.13	212.00
212.20	100.40	240.00
250.52	91.99	260.00
288.84	79.11	280.00
327.17	60.46	300.00
365.00	35.00	320.00

Rated Values

Head (m) 100.4

Mechanical Power 240




Efficiency (%)

Generate Synthetic Pump Curve

Generate

The detailed graph shows Head (m) on the left y-axis (0 to 150), Mechanical Power (kW) on the right y-axis (0 to 400), and Efficiency (%) on the far right y-axis (0 to 100). The x-axis is Flow (l/s) from 0 to 400. A blue curve represents Head, a red curve represents Mechanical Power, and a green curve represents Efficiency. A vertical line is drawn at the nominal flow of 212.20 l/s, showing a head of 100.4 m, mechanical power of 240 kW, and efficiency of approximately 85.5%.

# Case Study - Optimizer Plans








# Case Study - 7 day Cost Comparisons

Pumping Station 1 – 2.5% saving

Pumping Station 2 – 21.1 % Saving

Total – 11.5 % saving






- Optimised
- Baseline

7 day saving = £1.5k



# Case Study - Manual Plans Derived after the optimisation:

Pareto Results



## Optimisation Study Conclusions

Optimisation  
improves  
efficiency of the  
network

Provides the  
ability to find  
new ways to run  
the system

Next step  
towards near-  
real-time  
modelling  
capabilities



Thank you for listening

Are there any Questions?